

Husqvarna TR 48.



Applications.

- Ideal for large jobs to finish the concrete.
- Not recommended for use with a pan.

Benefits.

- Motor position places the weight in the center line of gravity so it is easier for the operator to control the machine.
- Speed Pitch, which allows the operator to instantly pitch the blades, is closer to the handle tube than previous models for easier access.
- Lifting bracket for easy lifting on and off the slab.
- Heavy-duty Viton™ seals in the gearbox can withstand high temperatures.
- Cast iron base for strength and longevity.
- Adjustable arms allow operator to easily modify arm if trowel is out of balance.
- A heavy-duty guard ring has a low profile for better balance and durability.
- Blade arms with universal bolt patterns for contractor convenience.

Technical specifications.

Power	9 hp*
Trowel diameter, in (mm)	48 (1,220)
Speed range, rpm	60 to 180
Pitch range	0 to 40°
Weight, lbs (kg)	281 (127)

*More technical specifications on page 203. *As rated by the engine manufacturer.*

Product specifications.

505472501, TR 48, 9 hp E
\$2,590

Accessories.

P

A	48" Gold combo blade	505495109	\$23.99
B	48" Finish blade	506957603	21.99
C	48" Silver combo blade	505495106	21.99
D	18" Float shoe	506957703	24.19



Combination blades.



Finish blades.



Silver combo blade.



Float shoes.